

2017-2019
Collection

studio
VINYL COLLECTION

PRESTIGE
300+



THE ULTIMATE
FLOORING EXPERIENCE

ELITE



EN 426 Roll width in m	EN 434 Dimensional stability	ISO 105/B02 Light fastness	Chemical resistance	EN 1815 Electrical behaviour	EN 660-2 Abrasion Group	Recyclable
3	≤ 0.40%	≥ 6	OK	≤ 2Kv	T	OK



EN 685 Domestic class	EN 685 Commercial class	EN 428 Thickness (mm)	EN 429 Wearlayer (mm)	EN 430 Weight (kg/m²)	EN 426 Roll length (m)	EN 433 Residual Indentation (mm)	EN 13501-1 Reaction to fire	ISO 717/2 Acoustic impact noise reduction	EN 425 Castor chair	DIN 51130 Slip resistance	EN 12524 Floor heating
		ca. 2.40	ca. 0.35	ca. 1.73	ca. 25	≤ 0.20	B ₁ -S1	ca. 16 dB	OK	R10	0.06 m² K/W

suitable for



AUS1221 ELITE
Although the utmost care is taken, the data here given could be imprecise and liable to modifications of a technical nature. In its strive to improve its floor solutions, Tarkett reserves the right to modify their technical specifications, colours and materials at any moment and without prior notice.